

WHAT IS CLAIMED IS:

1. A device for fixing the stem of a bicycle which is transported by a vehicle, said device comprising:

an expandable rod;

5 a first holder fastened with one end of the expandable rod for fixing the stem of the bicycle; and

a second holder fastened with other end of the expandable rod for fastening with the seat post of the bicycle;

wherein said first holder and said second holder are of
10 a U-shaped construction and are provided at a free end of one arm thereof with a confinement rod which is pivoted at one end thereof with the free end of the one arm, said confinement rod having other end which is engageable with a fastening knob, said first holder and said second holder being provided at a free
15 end of other arm thereof with a slot for locating releasably the other end of said confinement rod.

2. The device as defined in claim 1, wherein the free end of the other arm of said first holder and said second holder is provided with a stop portion for preventing the other end of said
20 confinement rod from moving out of said slot at the time when the other end of said confinement rod is located in said slot.

3. The device as defined in claim 1, wherein said first holder is provided with a restraining piece movably fastened therewith whereby said restraining piece is used to confine a
25 handlebar which is fastened with the stem of the bicycle.

4. The device as defined in claim 3, wherein said
restraining piece is provided at one end with a guide slot
engageable with the other end of said confinement rod in such a
manner that said restraining piece is located by said fastening
5 knob.

10

15

20

25